

Effective Light

Out Front. Pulling Away.



MINESPEC LED 360K-9

ECONOMIC LIGHT

50,000 hours of life for every light.

BUILT TOUGH

Built to the highest standards.

SUPER SAFE

Designed with the latest safety innovations.



ALLIGHT



Construction & Civil



Mining & Quarries



Rental



Industrial



Agriculture


THE SCIENCE OF LED LIGHTING

IN TODAY'S LED LIGHTING TOWER GAME THERE ARE THREE KINDS OF PLAYERS.

Those who make things happen, those who watch things happen, and those who wonder what happened.

WE KNOW WHERE WE STAND:

- No loss of light output after stabilisation.
Each LED flood light provides 60,000 effective lumens after stabilisation (IES standard - LM 79-08). Photometric Light Plots based on NATA approved testing parameters confidently state that the light output will match field testing.
- Perkins 2cyl water-cooled engine
- Extra low voltage (DC). OH&S risk elimination
- Stabilised power consumption of the LED is 450W nominal
- 6 x 450W low-glare lamps producing 360,000 lumens
- Refuel every 3 weeks
– on basis of 12hr operation each night
- 14t annual carbon footprint reduction per tower compared with metal halide equivalent
- SmartGen System (start/stop, location tracking and performance monitoring (optional))
- Complete plug and play system with no hard wired componentry makes for easy part and loom servicing or replacement
- 50,000 hours of life per light
- 500-hour service intervals
- Light instant-on (no warm-up/cool down)
- Made in Australia



MSLED 360K-9 STANDARD EQUIPMENT

Height	2.49m (8' 2")
Length	4.71m (15' 5")
Width	2.08m (6' 10")
Weight (Wet)	1,630kg (3,594lb)
Fuel	Diesel
Fuel Capacity	300L (79 US Gallons)
Fuel Tank	LLPDE
Fuel Consumption	1.27 L/hr (0.34US Gallons)
Engine	Perkins 403D-07
No. Engine Cylinders	3
Engine Aspiration	Naturally aspirated
Alternator	FB4-48/100
Power Generation	Extra low voltage (DC)
Electrical System	48
Number of Lights	6
Type of Lights	450W LEDs
Total Light Output	360,000 lumens
Light Tilt	Hydraulic
Mast Rotation	Manual
Mast Raise/Extension	9m (29' 6") Hydraulic
Trailer	Single axle
Tire and Rim Size	205 R16
Stabiliser Supports	4 x wind down
Tow Hitch	50mm ball (1.9") 2000kg (4409lb)
Also Includes	Battery isolation, emergency stop, timer shutdown

OPTIONS

Hydraulic light bar rotation	Wheel chocks
Hydraulic post rotation	Heavy duty drag skid
Hydraulic stabiliser legs	Twin axle trailer
CAT jumpstart	Coal mining wiring specs
Wiggins Fast Fill	Fire extinguisher

